



**DESCRIPTION**

An economical differential switch utilizing a simple and reliable design. It is used for many monitoring applications such as a filter change indicator. Constructed of an anodized aluminium body with steel ports for durability.

**FEATURES**

- Snap action micro switch
- Factory set or field adjustable
- Diaphragm design

**APPLICATIONS**

- Filter element monitoring
- Fluid control
- Water treatment applications


**Specifications**

Electrical	5A [12/24 VDC, 125 VAC] or 3A [250 VAC]
Switch Type	Snap Action
Protection	DIN 43650A - IP65, Terminals - IP00
Temperature Range	-20°F to 180°F (-29°C to 82°C) Nitrile
Mechanical Range	1,000,000 Cycles @ 75 PSI (5.2 BAR)
Diaphragm Material	Standard: Nitrile Optional: Viton, EPDM, HNBR
Housing Material	Anodized Aluminum Housing
Maximum Overpressure	500 PSI (34 BAR)
Repeatability	+/- 2% of full set point range
Differential	10 - 30% of setting
Weight	0.75 lbs (0.35 kg)

**Pressure Range**

Model	Adjustment Range	
	PSI	BAR
1	10 - 30	0.7 - 2.0
2	25 - 60	1.7 - 4.0

**Dimensions**



**Wiring Code**

CONTACT	DIN 43650 TYPE
COMMON	PIN 1
NORMALLY CLOSED	PIN 2
NORMALLY OPEN	PIN 3

## Ordering Information

Field Adjustable

DSPA - <sup>1</sup>2 - <sup>2</sup>4M-4M - <sup>3</sup>C - <sup>4</sup>HC - <sup>5</sup>1

### 1 - Pressure Selection:

Field Adjustable - Select Model Code

Insert set point value XXX followed by: R, F, BR, or BF

Model	Adjustment Range	
	PSI	BAR
1	10 - 30	0.7 - 2.0
2	25 - 60	1.7 - 4.0

OR

Set point	Direction	Description
XXXX	<b>R</b>	PSI Rising Pressure
	<b>F</b>	PSI Falling Pressure
	<b>BR</b>	BAR Rising Pressure
	<b>BF</b>	BAR Falling Pressure

### 2 - Thread Options for both process connections:

- 4M** - 1/4 NPT male , Plated Steel
- 4G** - 1/4 BSPP male, G1/4, Plated Steel

### 3 - Circuit:

- C** - SPDT (Single Pole Double Throw : Normally Open and Normally Closed)

### 4 - Electrical Termination:

- H** - DIN 43650A - connector type - male half only (only available in SPDT option)
- HC** - DIN 43650A PG9/PG11 - connector type (only available in SPDT option)
- HN** - DIN 43650A 1/2" NPT Conduit (only available in SPDT option)

### 5 - Options:

- 1** - Viton® Diaphragm
- 2** - EPDM Diaphragm
- 4** - HNBR Diaphragm
- 7** - Gold Contact, Snap Action Microswitch @ 20 mA / 12 VDC
- 8** - 10 amp, Snap Action Microswitch @ 10(2) 125 VAC (inductive)



Note: Please see page 42 for other available options